

Product: LAMINAM 5
Series: BLEND, COLLECTION, COLLECTION LUCIDATO, FOKOS, I NATURALI, KANKA, KOTAN, KAURI, OPIFICIO MEDICEO, OXIDE, TREDI



Laminam SpA
via Ghiarola Nuova, 258 Fiorano Modenese - MO - Italy
 12
 001DoP-5,6mm-151012

EN 14411:2012

Dry-pressed ceramic tiles with low water absorption
 $E_b \leq 0,5\%$, 5,6 mm nominal thickness
 for internal and external walls and floorings

Reaction to fire	A1 _{FL} - A1
Release of dangerous substances, for:	
– Cadmium	NPD
– Lead	NPD
Breaking strength	≥ 700 N
Slipperiness	DIN 51130
– Blend	R9
– Collection	R9
– Collection Lucidato	NPD
– Fokos	R9
– I Naturali	R9
– Kanka	R10
– Kotan	R10
– Kauri	R10
– Opificio Mediceo	R9

– Oxide	R9
– Tredi	R12
Tactility	NPD
Bond strength/adhesion, for:	
– Cementious adhesive, type C2S1/C2S2	1 N/mm ²
Thermal shock resistance	Pass
Durability, for:	
– Internal use	Pass
– External use: Freeze thaw resistance	Pass